



AKURATE

OVERVIEW

A high performance, multi-channel loudspeaker system

KEY FEATURES INCLUDE

- Linn 3K Driver Array* creates a consistent single point
- High quality 6 1/2 inch Sandwich cone drive units deliver pitch accurate, musical bass
- Acoustically matched double-flared ports with unique "rifled" design
- Unique Linn loudspeaker configuration system allows simple alternation between AKTIV and passive configuration
- Bass extension feature - allows complete flexibility to tailor bass response of AKURATE 242 and 225 to suit the listening environment
- AKURATE 221 Bass reinforcement loudspeaker deploys servo-controlled amplification and can be tailored to suit the listening environment
- A cast metal stand provides a solid, stable foundation for the floor standing AKURATE 242 and in conjunction with a column, supports the compact AKURATE 212 and AKURATE 225 loudspeakers

The AKURATE system consists of four distinct acoustically matched loudspeakers that can be simply configured for high performance stereo and multi-channel music or home theatre applications.

The AKURATE system has been designed to do full justice to the latest high-definition sound and vision formats, such as Super Audio CD. The system also combines the latest in Linn technology and high quality materials.

The full-range models within the AKURATE system, the 242, 225 and 212 loudspeakers, feature Linn's new 3K Driver Array* technology that creates a consistent single point sound source and improves high frequency response. All components used in the 3K Driver Array are tolerance matched to ensure sonic consistency throughout. Sandwich cone 6 1/2 inch bass drive units deliver pure musical bass and the highly braced internal cabinet construction ensures the best possible performance from the advanced drive unit design. These full range loudspeakers are stand mountable and come with invisible, flush fitting "SEKRIT-Fastener" grilles*.

In addition to three full-range models, the AKURATE system also includes the 221 - a bass reinforcement loudspeaker that deploys servo-controlled amplification. The 8 inch bass unit is constantly monitored and regulated to maintain accurate and musical bass in any listening environment.

All models are available in a choice of attractive finishes
 - Maple, Cherry, Rosenut and Black Ash.

* Patent pending




1



2



3



4

AKURATE

TECHNICAL SPECIFICATION

A high performance, multi-channel loudspeaker system



AKURATE 242

5 way Bass reflex floorstanding loudspeaker incorporating Linn 3K Driver Array and 2 x 6 1/2 inch Sandwich cone bass drivers

▮ Cabinet volume	42 litres
▮ Impedance (passive)	8 Ω
▮ Impedance (active bass)	16 Ω
▮ Impedance (active mid)	8 Ω
▮ Impedance (active tweeter)	6 Ω
▮ Impedance (active super tweeter)	4 Ω
▮ Efficiency	87 dB for 1 watt at 1 metre (1 kHz)
▮ Frequency response (passive)	49 Hz - 33 kHz
▮ Frequency response (active)	40 Hz - 33 kHz
▮ Magnetic shielding	yes
▮ Crossover options	Fully passive, partially or fully AKTIV
▮ Connection options	Up to 5 way by wire or amplifier, bass lift option when Bi-wiring, +/- 2 dB
▮ Dimensions	H 1000 x W 210 x D 380 mm H 39 1/2 x W 8 3/8 x D 15 inches
▮ Weight	32 kg / 70 1/2 lbs



AKURATE 212

4 way Bass reflex compact loudspeaker incorporating Linn 3K Driver Array and 1 x 6 1/2 inch Sandwich cone bass driver

▮ Cabinet volume	12 litres
▮ Impedance (passive)	8 Ω
▮ Impedance (active bass)	8 Ω
▮ Impedance (active mid)	8 Ω
▮ Impedance (active tweeter)	6 Ω
▮ Impedance (active super tweeter)	4 Ω
▮ Efficiency	87 dB for 1 watt at 1 metre (1 kHz)
▮ Frequency response (passive)	70 Hz - 33 kHz
▮ Frequency response (active)	50 Hz - 33 kHz
▮ Magnetic shielding	yes
▮ Crossover options	Fully passive, partially or fully AKTIV
▮ Connection options	Up to 4 way by wire or amplifier
▮ Dimensions	H 350 x W 210 x D 300 mm H 14 x W 8 3/8 x D 12 inches
▮ Weight	12 kg / 26 1/2 lbs

AKURATE 225

5 way centre channel/dialogue loudspeaker incorporating Linn 3K Driver Array and 2 x 6 1/2 inch Sandwich cone bass drivers

▮ Cabinet volume	25 litres
▮ Impedance (passive)	8 Ω
▮ Impedance (active bass)	16 Ω
▮ Impedance (active mid)	8 Ω
▮ Impedance (active tweeter)	6 Ω
▮ Impedance (active super tweeter)	4 Ω
▮ Efficiency	87 dB for 1 watt at 1 metre (1 kHz)
▮ Frequency response (passive)	66 Hz - 33k Hz
▮ Frequency response (active)	58 Hz - 33 kHz
▮ Magnetic shielding	yes
▮ Crossover options	Fully passive, partially or fully AKTIV
▮ Connection options	Up to 5 way by wire or amplifier, bass lift option when Bi-wiring, +/- 2 dB
▮ Dimensions	H 250 x W 600 x D 300 mm H 9 7/8 x W 23 3/4 D 12 inches
▮ Weight	21 kg / 46 3/8 lbs



AKURATE 221

8 inch Bass reinforcement loudspeaker utilising 500 watts of servo-assisted Linn silent power.

▮ Drive Unit	8 inch servo-assisted bass
▮ Cabinet volume	21 litres
▮ Mains input voltage range	100 V: 90 - 110 V 115 V: 103 - 126 V 230 V: 207 - 253 V
▮ Mains supply frequency	50 - 60 Hz
▮ External frequency response	Adjustable from 10 Hz -235 Hz in 9 steps. Default is 10 Hz
▮ Internal frequency response:	Adjustable from 55 Hz -130 Hz in 3 steps and flat (to allow external low pass filtering). Default is 85 Hz
▮ Gain	Adjustable in 1 dB steps
▮ Line input impedance	18 kΩ
▮ Line output level	Electronically in parallel with line input
▮ Output power	500 W RMS, 1000 W peak
▮ Magnetic shielding	yes
▮ Control features	Signal sensing, auto on/off
▮ Protection	Fully protected against overload, over temperature, full short circuit and overdrive
▮ Dimensions	H 324 x W 324 x D 324 mm H 12 3/4 x W 12 3/4 x D 12 3/4 inches
▮ Weight	17 kg / 37 1/2 lbs

The above information is subject to change without prior notice.

Linn Products Ltd

Glasgow Road, Waterfoot, Eaglesham, Glasgow G76 0EQ, Scotland, UK.

Telephone: +44 (0) 141 307 7777, Facsimile: +44 (0) 141 644 4262, Helpline: 0500 888909, E-mail: helpline@linn.co.uk, Website: www.linn.co.uk

Linn Products Inc

8787 Perimeter Park Boulevard, Jacksonville FL 32216, USA.

Telephone: +1 (904) 645 5242, Facsimile: +1 (904) 645 7275, Helpline: 888-671-LINN, E-mail: helpline@linninc.com, Website: www.linninc.com

Linn Deutschland GmbH

Hühnerposten 1d, 20097 Hamburg, Deutschland.

Telephone: +49 (0) 40 890 660 0, Facsimile: +49 (0) 40 890 660 29, E-mail: info@linngmbh.de, Website: www.linn.co.uk

Linn Records Ltd

Glasgow Road, Waterfoot, Eaglesham, Glasgow G76 0EQ, Scotland, UK. Telephone: +44 (0) 141 303 5435, Facsimile: +44 (0) 141 303 5007,

Helpline/Mail order: +44 (0) 141 303 5027, E-mail: records@linn.co.uk, Website: www.linnrecords.com

© 2005, Linn Products Limited. All rights reserved.

Linn, the Linn logo, and AKURATE are trade marks of Linn Products Limited, registered (in at least the UK and/or the EU) or unregistered trade marks of Linn Products Limited.

Linn Products Limited disclaims any proprietary interest in trade marks and trade names other than its own.

PACK 915 (10/05)